## NSN 5935-01-222-1094

Plug Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-222-1094

**Body Style:** 

Straight shape

**Overall Length:** 

2.850 inches

**Overall Width:** 

0.250 inches

**Environmental Protection:** 

Vibration resistant and shock resistant and salt water resistant and humidity resistant

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Guide pin/socket

Shell Type:

Potting

**Connector Locking Method:** 

Friction

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Glass fiber and plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Criticality Code Justification:** 

Feat

**Contact Material Specification:** 

Qq-c-530 federal specification single material response or qq-c-533 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, ty gdi-30f or ty sdg-f military specification all material responses single mating end

**Included Contact Quantity:** 

40 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

Special Features:

The following contacts are shorted together; 1, 2; 2, 3; 3, 4; 4, 5; 5, 6; 6, 7; 7, 8; 8, 9; 9, 10; 10, 11; 11, 12; 12, 13; 13, 14; 14, 15; 15, 16; 16, 17; 17, 18; 18, 19; 19, 20; 20, 21; 21, 22; 23, 24; 24, 25; 25, 26; 26, 27; 27, 28; 28, 29; 29, 30; 30, 31; 31, 32; 32, 33; 34; 34, 35; 35, 36; 36; 36; 37; 37, 38; 38, 30; 30, 40

## NSN 5935-01-222-1094

Plug Dummy Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material And Weight:
0.040 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.