Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-222-2271

# Thread Class:

2a

**Thread Direction:** 

Right-hand

## **Body Style:**

Straight shape, latching

## **Overall Length:**

2.062 inches

#### **Bushing Diameter:**

0.438 inches

#### Diameter:

1.000 inches

#### **Environmental Protection:**

Watertight

#### **Threaded Device Type:**

## Mounting bushing

Mating End Quantity:

1

## **Contact Position Arrangement Style:**

Nonstd single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

## Contact Maximum Current Rating In Amps:

15.0 single mating end single contact grouping

### Contact Maximum Ac Voltage Rating In Volts:

240.0 single mating end single contact grouping

#### **Polarization Method:**

Mating end

#### Shell Type:

Solid

### **Connector Locking Method:**

Friction

### Thready Qty Per Inch (tpi):

20

## Thread Size:

0.438 inches

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

## **Insert Material:**

Rubber natural single mating end

Electrical Receptacle Connector - Page 2 of 2



Shell Material:

Rubber natural

Included Contact Quantity:

2 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round

Included Contact Type:

Round socket single mating end single contact grouping

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A039b0