## NSN 5935-01-222-3308

**Thread Class:** 

2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-222-3308

Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
31.0 millimeters
Overall Diameter:
38.5 millimeters
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
19-35 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
End Application:
5895-00-222-4224
Thread Length:
000 = 0.19
0.219 inches
•
0.219 inches
0.219 inches Thready Qty Per Inch (tpi):
0.219 inches  Thready Qty Per Inch (tpi):  10
0.219 inches  Thready Qty Per Inch (tpi):  10  Thread Size:
0.219 inches  Thready Qty Per Inch (tpi):  10  Thread Size:  28.0 millimeters and 1.250 inches
0.219 inches Thready Qty Per Inch (tpi): 10 Thread Size: 28.0 millimeters and 1.250 inches Thread Pitch In Millimeters:
0.219 inches  Thready Qty Per Inch (tpi):  10  Thread Size:  28.0 millimeters and 1.250 inches  Thread Pitch In Millimeters:  1.00
0.219 inches Thready Qty Per Inch (tpi): 10 Thread Size: 28.0 millimeters and 1.250 inches Thread Pitch In Millimeters: 1.00 Terminal Location:
0.219 inches  Thready Qty Per Inch (tpi):  10  Thread Size:  28.0 millimeters and 1.250 inches  Thread Pitch In Millimeters:  1.00  Terminal Location:  Back single mating end single contact grouping
0.219 inches  Thready Qty Per Inch (tpi):  10  Thread Size:  28.0 millimeters and 1.250 inches  Thread Pitch In Millimeters:  1.00  Terminal Location:  Back single mating end single contact grouping  Contact Material:

## **NSN 5935-01-222-3308**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Thread Tolerance Class:
6g external
Included Contact Quantity:
66 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.066 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
lso m and special acme
Specification Data:
81349-mil-dtl-38999/26 government specification
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A039b0