

View Online at <https://aerobasegroup.com/nsn/5935-01-222-3582>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

2.219 inches

**Overall Diameter:**

2.188 inches

**Distance From Mounting Shoulder To Front Face:**

1.696 inches

**Mounting Facility Thickness:**

Between 0.125 inches and 0.750 inches

**Threaded Device Type:**

Back shell and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

25-61 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

345.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Thready Qty Per Inch (tpi):**

18 and 18

**Thread Size:**

1.437 inches and 1.750 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Nickel alloy single mating end 2nd contact grouping

**Contact Surface Treatment:**

Gold single mating end 3rd contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end 3rd contact grouping

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Nickel or cadmium

**Shell Surface Treatment Specification:**

Mil-c-26074 military specification single treatment response or qq-p-416 federal specification single treatment response

**Included Contact Quantity:**

59 single mating end 3rd contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.059 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef and uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.