Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-223-0384

sody Style:	
traight shape	
Overall Length:	
.185 inches	
Overall Width:	
.308 inches	
Inthreaded Mounting Hole Diameter:	
.091 inches	
Distance Between Mounting Facility Centers:	
.965 inches	
lating End Quantity:	
Contact Position Arrangement Style:	
5 single mating end	
Contact Removability:	
Ionremovable single mating end single contact grouping	
olarization Method:	
fating end	
hell Type:	
Solid	
connector Locking Method:	
riction	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
old single mating end single contact grouping	
nsert Material:	
lastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end	
criticality Code Justification:	
eat	
shell Material:	
luminum alloy	
chell Surface Treatment:	
Cadmium and chromate	
chell Surface Treatment Specification:	
Qq-p-416, type 2, cl 3 federal specification all treatment responses	
hell Material Specification:	
Qq-a-591 federal specification single material response or qq-a-200 federal specification single material response	
nsert Material Specification:	
1il-m-14, ty sdg-f military specification 1st material response single mating end and mil-m-14, ty sdg-f military specification	on 2nd material
esponse single mating end or mil-m-24519 military specification 3rd material response single mating end	
pecial Features:	
he following contacts are shorted together; 1, 3; 2, 25; 4, 17; 6, 7; 10, 12; 11, 15; 13, 16; 14, 22; 18, 23; 19, 24; 2	20, 21



Precious Material And Location:

Contact surfaces gold

#### **Precious Material And Weight:**

0.025 gold grains, troy

# Precious Material:

Gold

# Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14 spec.