Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-223-3070

Body Style: Straight shape, external coupling **Overall Length:** 1.247 inches **Overall Height:** Between 1.552 inches and 1.573 inches **Overall Width:** Between 1.552 inches and 1.573 inches **Environmental Protection:** Thermal shock resistant and moisture resistant and salt water resistant and vibration resistant and shock resistant and fungus resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** Between 0.442 inches and 0.447 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 22-55 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 334.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **End Application:** 1430-01-191-8780 **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping



Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and nickel **Shell Surface Treatment Specification:** Qq-p-416 federal specification 1st treatment response **Included Contact Quantity:** 55 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.055 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.