NSN 5935-01-223-3972 Tip. lack - Page 1 of 2



| TIP Jack - Page 1 01 2 | Gru |
|---|-----|
| View Online at https://aerobasegroup.com/nsn/5935-01-223-3972 | |
| Electrical Insulation Feature: | |
| Insulated completely | |
| Identification Code Color: | |
| Gray | |
| Body Style: | |
| Terminal mounted | |
| Overall Length: | |
| 0.460 inches | |
| Terminal Length: | |
| 0.130 inches | |
| Overall Height: | |
| 0.350 inches | |
| Overall Width: | |
| 0.156 inches | |
| Distance Between Mounting Facility Centers: | |
| 0.400 inches | |
| Maximum Voltage Rating In Volts: | |
| 1500.0 ac | |
| Accommodated Finger Type: | |
| Test prod single finger | |
| Finger Accommodation Diameter: | |
| 0.080 inches single finger | |
| Finger Accommodation Length: | |
| 0.460 inches single finger | |
| Current Rating In Amps: | |
| 5.0 | |
| Mounting Facility Type And Quantity: | |
| 2 terminal | |
| Terminal Type: | |
| Pin | |
| Material: | |
| Copper alloy terminal | |
| Material: | |
| Plastic polyamide insulator | |
| Precious Material And Location: | |
| Contact surface gold | |
| Precious Material And Weight | |

Gold

Surface Treatment:

0.001 gold grains, troy **Precious Material:**

Gold spring

NSN 5935-01-223-3972

Tip Jack - Page 2 of 2



| Surface Treatmer |
|------------------|
|------------------|

Gold spring

Test Data Document:

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-39024/11 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400