NSN 5935-01-223-4052

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-223-4052

Body Style:

Straight shape w/solder mount

Overall Length:

1.216 inches

Overall Diameter:

1.312 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

19-35 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 95.0 and 132.0 and 232.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Operating Tempurature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Nickel single mating end single contact grouping and iron alloy 52 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Tin

Shell Surface Treatment Specification:

Mil-t-10727, type 1 military specification single treatment response

Included Contact Quantity:

66 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

NSN 5935-01-223-4052

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Solder flange mount
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.066 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27471 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.