NSN 5935-01-223-4620

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-223-4620

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Straight shape
Overall Length:
0.780 inches
Overall Width:
0.215 inches
Environmental Protection:
Corrosion resistant and cold resistant and heat resistant and vibration resistant
Distance Between Mounting Facility Centers:
0.565 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
9 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-01-223-4620

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy 380.0
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074, cl 3 military specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-m-14, ty sdg-f military specification all material responses single mating end
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.