Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-223-4846

| Body Style: |
|--|
| Straight shape |
| Overall Length: |
| 2.500 inches |
| Overall Height: |
| 1.310 inches |
| Overall Width: |
| 1.840 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.187 inches |
| Distance Between Mounting Facility Centers: |
| 2.000 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| "3, 5-20" single mating end |
| Contact Removability: |
| Nonremovable single mating end all contact groupings |
| Contact Maximum Current Rating In Amps: |
| 20.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 125.0 single mating end single contact grouping |
| Polarization Method: |
| Contact to contact polarizing keys |
| Shell Type: |
| Solid |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Material: |
| Copper alloy 230 single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Terminal Type: |
| Screw single mating end all contact groupings |
| Shell Material: |
| Steel |
| Included Contact Quantity: |
| 1 single mating end all contact groupings |
| Included Contact Type: |
| T-socket single mating end 3rd contact grouping |
| Shelf Life: |
| N/a |
| 170 |

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0