## NSN 5935-01-223-6392

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-223-6392

**Body Style:** 

Straight type

**Overall Length:** 

195.45 millimeters

**Overall Height:** 

17.02 millimeters

**Overall Width:** 

13.72 millimeters

**Distance Between Mounting Facility Centers:** 

Between 187.08 millimeters and 187.58 millimeters

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Contact to contact polarizing keys

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic polyester single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-530 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-p-46161 military specification single material response single mating end

**Included Contact Quantity:** 

128 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

## NSN 5935-01-223-6392

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.128 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.