NSN 5935-01-223-9359

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-223-9359 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.561 inches and 1.601 inches **Overall Height:** 2.500 inches **Overall Width:** 2.500 inches **Environmental Protection:** Corrosion resistant and moisture resistant and thermal shock resistant and vibration resistant and shock resistant **Unthreaded Mounting Hole Diameter:** Between 0.171 inches and 0.177 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.938 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.938 inches **Distance From Mounting Shoulder To Front Face:** Between 0.875 inches and 0.885 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 36-77 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 80.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 280.0

Solid

Shell Type:

NSN 5935-01-223-9359

Electrical Receptacle Connector - Page 2 of 3



| Connector Locking Method: |
|--|
| Externally threaded shell |
| |
| End Application: |
| Qq29 (v) 2/msm |
| Thready Qty Per Inch (tpi): |
| 16 Thread Sings |
| Thread Size: |
| 2.250 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Silver single mating end single contact grouping |
| Insert Material: |
| Rubber synthetic single mating end |
| Contact Surface Treatment Specification: |
| Qq-s-365 federal specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium and chromate |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 2, class 3 federal specification all treatment responses |
| Included Contact Quantity: |
| 7 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material And Weight: |
| 0.035 silver grains, troy |
| Precious Material: |
| Silver |
| Thread Series Designator: |
| Un |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5935-01-223-9359

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0