

View Online at <https://aerobasegroup.com/nsn/5935-01-224-5293>

Body Style:

Straight shape

Overall Length:

0.734 inches

Overall Diameter:

0.250 inches

Environmental Protection:

Vibration resistant and shock resistant and salt water resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

Smb single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Snap ring

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204 military specification single treatment response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and shell surfaces gold and clamp collet surface silver

Precious Material And Weight:

0.105 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.