

View Online at <https://aerobasegroup.com/nsn/5935-01-224-5313>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

2.200 inches

Overall Diameter:

1.641 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock proof and vibration proof

Distance From Mounting Shoulder To Front Face:

Between 0.761 inches and 0.781 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.125 inches

Threaded Device Type:

Back shell and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

31 number 20 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

24.0 and 135.0 and 199.0 and 240.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

1.062 inches and 1.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, cl 3 or 4, grade b military specification single treatment response

Shell Material Specification:

Qq-a-367 federal specification single material response

Included Contact Quantity:

31 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.031 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

81349-mil-c-83723/74 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-std-15504