

View Online at <https://aerobasegroup.com/nsn/5935-01-224-6545>

**Body Style:**

Straight type

**Overall Length:**

Between 5.110 inches and 5.140 inches

**Overall Height:**

Between 0.776 inches and 0.816 inches

**Overall Width:**

Between 0.495 inches and 0.505 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.143 inches and 0.149 inches

**Distance Between Mounting Facility Centers:**

4.525 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

**Shell Surface Treatment:**

Chromate

**Shell Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification single treatment response

**Included Contact Quantity:**

56 single mating end single contact grouping

**Included Contact Type:**

Spring pincers single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.056 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.