Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-224-7482

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.531 inches
Overall Height:
Between 1.969 inches and 2.031 inches
Overall Width:
Between 1.969 inches and 2.031 inches
Unthreaded Mounting Hole Diameter:
Between 0.145 inches and 0.151 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.557 inches and 1.567 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.557 inches and 1.567 inches
Distance From Mounting Shoulder To Front Face:
Between 0.812 inches and 0.822 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
1.750 inches
Terminal Location:
Back single mating end single contact grouping

NSN 5935-01-224-7482

Electrical Receptacle Connector - Page 2 of 2



-	ontact Material:
	opper alloy single mating end single contact grouping ontact Surface Treatment:
	ilver single mating end single contact grouping
	isert Material:
	ubber single mating end
	ontact Surface Treatment Specification: q-s-365 federal specification single treatment response single mating end single contact grouping
	erminal Type:
	older well single mating end single contact grouping
	hell Material:
	luminum alloy
	hell Surface Treatment:
	admium and chromate
-	hell Surface Treatment Specification:
	q-p-416, type ii, class 3 federal specification all treatment responses
	sert Material Specification:
	lil-r-3065 military specification single material response single mating end
	icluded Contact Type:
	ound pin single mating end single contact grouping
	recious Material And Location:
C	ontact surfaces silver
P	recious Material:
Si	ilver
Tł	hread Series Designator:
U	ns
SI	helf Life:
N/	/a
U	nit Of Measure:
D	emilitarization:
N	0
Fi	iig:
A	039b0
Μ	il-std (military Standard):
Μ	lil-r-3065 spec.