Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-225-1340

view online at https://delobasegroup.com/hsi//0000 01 220 1040	
Body Style:	
Straight type	
Overall Length:	
0.690 inches	
Overall Width:	
0.294 inches	
Body Height:	
0.440 inches	
Environmental Protection:	
Shock resistant and vibration resistant	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
2 rows of contacts non-inserted board single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
3.0 single mating end single contact grouping	
Connector Locking Method:	
Friction	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping and nickel single mating end single contact grouping	
Insert Material:	
Glass single mating end and plastic polyamide single mating end	
Contact Surface Treatment Specification:	
Mil-g-45204, ty ii, cl o, grade c military specification 1st treatment response single mating end single contact grouping	l
Terminal Type:	
Tab, solder lug single mating end single contact grouping	
Contact Material Specification:	
Qq-c-530 federal specification single material response single mating end single contact grouping	
Included Contact Quantity:	
10 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.010 gold grains, troy	

Electrical Receptacle Connector - Page 2 of 2



Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.