Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-225-1908

Body Style:
Right angle type
Overall Length:
3.346 inches
Overall Width:
0.750 inches
Body Height:
0.468 inches
Unthreaded Mounting Hole Diameter:
0.144 inches
Distance Between Mounting Facility Centers:
3.000 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
650.0 single mating end single contact grouping
Polarization Method:
Mating end and guide pin/socket
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 2 military specification 1st treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Aluminum alloy

NSN 5935-01-225-1908

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2 federal specification single treatment response **Shell Material Specification:** Qq-a-591 federal specification single material response **Insert Material Specification:** Mil-p-19833, ty gdi-30f military specification all material responses single mating end Shell Guide Type And Location Designator: F pin **Included Contact Quantity:** 15 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.015 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.