NSN 5935-01-225-1912

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-225-1912

Straight shape
Overall Length:
3.842 inches
Overall Height:
0.670 inches
Overall Width:
0.438 inches
Unthreaded Mounting Hole Diameter:
0.144 inches
Distance Between Mounting Facility Centers:
3.436 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
650.0 single mating end single contact grouping
Polarization Method:
Mating end and guide pin/socket and shell
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 2 military specification 1st treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Aluminum alloy

NSN 5935-01-225-1912

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-p-19833, ty gdi-30f military specification all material responses single mating end
Shell Guide Type And Location Designator:
K pin and c slot
Included Contact Quantity:
15 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces and polarizing pin surface gold
Precious Material And Weight:
0.016 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):