NSN 5935-01-225-6834

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-225-6834

Body Style: Straight edge type **Overall Length:** 2.960 inches **Overall Height:** 0.700 inches **Overall Width:** 0.400 inches **Environmental Protection:** Heat resistant and cold resistant **Board Accommodated Length:** 2.605 inches single board **Board Accommodated Width:** 0.062 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Connector Locking Method:** Friction **Connector Cable Strain Relief Method:** Integral clamp **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic polyester single mating end and glass fiber single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Included Contact Quantity:** 50 single mating end single contact grouping **Included Contact Type:** Bifurcated spring single mating end single contact grouping

Special Features:

Polarization provided by optional polarization key

NSN 5935-01-225-6834

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.