

View Online at <https://aerobasegroup.com/nsn/5935-01-226-1986>

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

0.781 inches

**Environmental Protection:**

Watertight

**Cable Entrance Diameter:**

Between 0.390 inches and 1.375 inches

**Mating End Quantity:**

1

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

60.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Spring friction

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0