# NSN 5935-01-226-2598

Thread Class: 2a and 2b

Right-hand **Body Style:** 

**Thread Direction:** 

Straight shape w/screw locks

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-226-2598

Overall Length:
Between 0.860 inches and 0.900 inches
Overall Height:
Between 0.510 inches and 0.550 inches
Overall Width:
Between 0.250 inches and 0.290 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
14 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1800.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end or glass fiber single mating end

## NSN 5935-01-226-2598

Electrical Plug Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:** 

Stainless steel

## **Shell Material Specification:**

Qq-s-763 federal specification single material response

## **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

#### **Included Contact Quantity:**

14 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

#### **Precious Material And Weight:**

0.014 gold grains, troy and 0.014 silver grains, troy

#### **Precious Material:**

Gold and silver

## **Thread Series Designator:**

Unc

## Shelf Life:

N/a

## Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.