NSN 5935-01-226-4288

Thread Class: 2a and 2a

Body Style:

Overall Length: 1.115 inches

Overall Diameter:

Thread Direction:

Right-hand and right-hand

Straight shape threaded

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-226-4288

0.577 inches
Environmental Protection:
Salt water resistant
Mounting Facility Thickness:
0.100 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
32 and 32
Thread Size:
0.375 inches and 0.375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping

NSN 5935-01-226-4288

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, ty ii federal specification all treatment responses
Shell Material Specification:
Qq-c-530 federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round socket single mating end single contact grouping
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0