NSN 5935-01-226-8368

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-226-8368 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight type **Overall Length: 3.795** inches **Overall Height:** 0.670 inches **Overall Width:** 0.490 inches **Environmental Protection:** Shock resistant and humidity resistant and salt water resistant and cold resistant and heat resistant **Distance Between Mounting Facility Centers:** 3.475 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1300.0 single mating end single contact grouping **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): Thread Size: 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 1 military specification 1st treatment response single mating end single contact grouping **Terminal Type:**

Crimp single mating end single contact grouping

NSN 5935-01-226-8368

Electrical Receptacle Connector - Page 2 of 2



Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-p-46161, cl 15, grade b military specification single material response single mating end

Included Contact Quantity:

75 single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.075 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.