

View Online at <https://aerobasegroup.com/nsn/5935-01-226-8370>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight type

**Overall Length:**

2.295 inches

**Overall Height:**

0.670 inches

**Overall Width:**

0.490 inches

**Environmental Protection:**

Shock resistant and humidity resistant and salt water resistant and cold resistant and heat resistant

**Distance Between Mounting Facility Centers:**

1.975 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1300.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-p-46161, cl 15, grade b military specification single material response single mating end

**Included Contact Quantity:**

30 single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.030 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.