

View Online at <https://aerobasegroup.com/nsn/5935-01-226-9968>

**Body Style:**

Straight shape

**Overall Length:**

8.050 inches

**Overall Height:**

2.025 inches

**Overall Width:**

0.740 inches

**Environmental Protection:**

Humidity resistant and vibration resistant and shock resistant and heat resistant and cold resistant

**Unthreaded Mounting Hole Diameter:**

0.067 inches

**Distance Between Mounting Facility Centers:**

7.590 inches

**Mating End Quantity:**

1

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

5.0 single mating end 2nd contact grouping

**Polarization Method:**

Mating end

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end 2nd contact grouping

**Contact Surface Treatment:**

Gold single mating end all contact groupings and nickel single mating end all contact groupings

**Insert Material:**

Plastic polyester single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end all contact groupings and qq-n-290 federal specification 2nd treatment response single mating end all contact groupings

**Terminal Type:**

Pin single mating end 1st contact grouping

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end 2nd contact grouping

**Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

**Included Contact Quantity:**

27 single mating end 2nd contact grouping

**Included Contact Type:**

Round pin single mating end 2nd contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.043 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-c-50 spec.