

View Online at <https://aerobasegroup.com/nsn/5935-01-227-1886>

Body Style:

Straight shape

Overall Length:

0.370 inches

Overall Diameter:

0.166 inches

Environmental Protection:

Thermal shock resistant and vibration resistant and shock resistant and corrosion resistant

Mating End Quantity:

2

Contact Position Arrangement Style:

Smc all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and copper all mating ends single contact grouping

Insert Material:

Plastic fluorocarbon all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 1 military specification 1st treatment response all mating ends single contact grouping and mil-c-14550 military specification 2nd treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response all mating ends single contact grouping

Shell Material:

Steel comp 303

Shell Surface Treatment:

Passivate

Shell Material Specification:

Astm 582, cond a assn standard single material response

Insert Material Specification:

L-p-403 federal specification single material response all mating ends

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.