# NSN 5935-01-227-4092

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-227-4092 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.312 inches **Overall Height:** 2.031 inches **Overall Width:** 2.031 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches **Distance From Mounting Shoulder To Front Face:** 0.827 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Maximum Current Rating In Amps:** 20.0 single mating end 2nd contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1050.0 single mating end 2nd contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Screw **Thread Length:** 0.827 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.750 inches **Terminal Location:** 

reminal Eccation.

Back single mating end 2nd contact grouping

# NSN 5935-01-227-4092

Electrical Receptacle Connector - Page 2 of 2



_							
т-	Λn	+-	rt.	ΝЛ	210	eria	
•	VII	ιca	·ι	IVI	au	zı ıa	и.

Steel single mating end 2nd contact grouping

#### **Contact Surface Treatment:**

Nickel single mating end 2nd contact grouping and silver single mating end 2nd contact grouping and gold single mating end 2nd contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

# **Terminal Type:**

Solder well single mating end 2nd contact grouping

# **Shell Material:**

Aluminum alloy

#### **Included Contact Quantity:**

9 single mating end all contact groupings

# **Special Features:**

Four contacts in center with dielectric barrier between these and five contacts in circle outside diameter

# **Thread Series Designator:**

Uns

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0