NSN 5935-01-227-7751

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-227-7751

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight type
Overall Length:
5.295 inches
Overall Height:
0.670 inches
Overall Width:
0.590 inches
Environmental Protection:
Shock resistant and vibration resistant and humidity resistant and corrosion resistant
Distance Between Mounting Facility Centers:
4.975 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type ii military specification 1st treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping

NSN 5935-01-227-7751

Electrical Receptacle Connector - Page 2 of 2



Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-p-46161, class 15, grade b military specification single material response single mating end

Included Contact Quantity:

160 single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.160 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.