

View Online at <https://aerobasegroup.com/nsn/5935-01-227-8505>

Thread Class:

2a and 3b

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

31.5 millimeters

Overall Height:

46.0 millimeters

Overall Width:

46.0 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 34.93 millimeters and 38.10 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 34.93 millimeters and 38.10 millimeters

Distance From Mounting Shoulder To Front Face:

20.1 millimeters

Threaded Device Type:

Back shell and coupling facility and hub

Mating End Quantity:

12

Polarization Method:

Keyway or multiple keyway and key, multiple key groove

Insert Position In Deg:

0.0 and 95.0 and 132.0 and 232.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

10 and 32 and 18

Thread Size:

37.0 millimeters and 1.625 inches

Thread Pitch In Millimeters:

1.00 and 1.00

Shell Material:

Aluminum alloy or zinc

Shell Surface Treatment:

Cadmium and chromate and zinc

Shell Surface Treatment Specification:

Qq-p-416 ty ii, cl 3 federal specification single treatment response

Thread Tolerance Class:

6g external and 6h external

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m and special acme

Specification Data:

81349-dod-c-38999/20 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0