NSN 5935-01-228-3043

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-228-3043

| Thread Class: |
|--------------------------------------------------------------------------------------------------------------------|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 1.500 inches |
| Overall Diameter: |
| Between 0.620 inches and 0.630 inches |
| Environmental Protection: |
| Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 2 |
| Contact Position Arrangement Style: |
| Tnc all mating ends |
| Contact Removability: |
| Nonremovable all mating ends single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling nut |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 50.0 all mating ends single contact grouping |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.438 inches |
| Contact Surface Treatment: |
| Gold all mating ends single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 2, cl 1 military specification single treatment response all mating ends single contact grouping |
| Shell Material: |
| Metal |
| Included Contact Quantity: |
| 1 2nd mating end single contact grouping |
| Included Contact Type: |
| Coaxial pin all mating ends single contact grouping |
| Precious Material And Location: |

Contact surfaces gold

NSN 5935-01-228-3043

Connector Adapter - Page 2 of 2



| Precious Material And Weight: |
|-------------------------------|
| 0.010 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-g-45204 spec.