NSN 5935-01-229-0295



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-229-0295 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.312 inches **Overall Height:** 2.031 inches **Overall Width:** 2.031 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches **Distance From Mounting Shoulder To Front Face:** 0.827 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Maximum Current Rating In Amps:** 20.0 single mating end 2nd contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1050.0 single mating end 2nd contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 180.0 Shell Type: **Connector Locking Method:** Screw **Thread Length:** 0.827 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.750 inches

Terminal Location:

Back single mating end 2nd contact grouping

NSN 5935-01-229-0295

Electrical Receptacle Connector - Page 2 of 2



_							
r -	n	+-	rt.	N/I	atα	ria	
·	OI.	ιa	·ι	IVI	alc	ııа	ı .

Steel single mating end 2nd contact grouping

Contact Surface Treatment:

Nickel single mating end 2nd contact grouping and silver single mating end 2nd contact grouping and gold single mating end 2nd contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end 6th contact grouping

Shell Material:

Aluminum alloy

Included Contact Quantity:

9 single mating end all contact groupings

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0