## NSN 5935-01-229-2752

Anodize

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-229-2752

Body Style:
Right angle type
Overall Length:
5.540 inches
Overall Height:
0.343 inches
Overall Width:
0.580 inches
Environmental Protection:
Vibration resistant and shock resistant and salt water resistant and humidity resistant
Unthreaded Mounting Hole Diameter:
Between 0.094 inches and 0.100 inches
Distance Between Mounting Facility Centers:
5.340 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Guide pin/socket
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:

## NSN 5935-01-229-2752

Electrical Receptacle Connector - Page 2 of 2



## **Shell Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Unable To Decode:** 

Unable to decode and unable to decode

**Included Contact Quantity:** 

100 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.100 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.