NSN 5935-01-229-2890

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-229-2890 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight edge type w/mounting flange **Overall Length:** 4.475 inches **Overall Height:** 0.656 inches **Overall Width:** 0.400 inches **Distance Between Mounting Facility Centers: 4.175** inches **Board Accommodated Length:** 3.700 inches single board **Threaded Device Type:** Mounting hole **Board Accommodated Width:** 0.062 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Connector Locking Method:** Friction **End Application:** Satellite communication terminal Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:**

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-229-2890

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Included Contact Quantity:
72 single mating end single contact grouping
Included Contact Type:
Bifurcated spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.072 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0