## NSN 5935-01-229-3949

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-229-3949

**Body Style:** Straight shape, external coupling **Overall Length:** Between 1.024 inches and 1.044 inches **Overall Height:** 1.031 inches **Overall Width:** 1.031 inches **Unthreaded Mounting Hole Diameter:** Between 0.123 inches and 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Distance From Mounting Shoulder To Front Face:** Between 0.627 inches and 0.632 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 36100 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 332.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** 

Shell Material:

Crimp single mating end single contact grouping

Aluminum alloy

## NSN 5935-01-229-3949

Electrical Receptacle Connector - Page 2 of 2



Passivate  Included Contact Quantity: 6 single mating end single contact grouping  Included Contact Type: Round pin single mating end single contact grouping  Precious Material And Location: Contact surfaces gold  Precious Material And Weight: 0.030 gold grains, troy  Precious Material: Gold  Test Data Document: 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in speciformat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Included Contact Type: Round pin single mating end single contact grouping  Precious Material And Location: Contact surfaces gold  Precious Material And Weight: 0.030 gold grains, troy  Precious Material: Gold  Test Data Document: 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in speciformat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Included Contact Type:  Round pin single mating end single contact grouping  Precious Material And Location:  Contact surfaces gold  Precious Material And Weight:  0.030 gold grains, troy  Precious Material:  Gold  Test Data Document:  81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in speciformat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Round pin single mating end single contact grouping  Precious Material And Location:  Contact surfaces gold  Precious Material And Weight:  0.030 gold grains, troy  Precious Material:  Gold  Test Data Document:  81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in speciformat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Precious Material And Location:  Contact surfaces gold  Precious Material And Weight:  0.030 gold grains, troy  Precious Material:  Gold  Test Data Document:  81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in speciformat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Contact surfaces gold  Precious Material And Weight:  0.030 gold grains, troy  Precious Material:  Gold  Test Data Document:  81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in speciformat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Precious Material And Weight:  0.030 gold grains, troy  Precious Material:  Gold  Test Data Document:  81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in speciformat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
0.030 gold grains, troy  Precious Material:  Gold  Test Data Document:  81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Precious Material:  Gold  Test Data Document:  81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificant; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Gold  Test Data Document:  81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in speciformat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
<b>Test Data Document:</b> 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cerenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	cificatio
	ain
Specification Data:	
96906-ms27496 government standard	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	