Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-229-7190

2a Thread Direction: Right-hand Body Style: Straight shape, external coupling Overall Length: . 1.400 inches Overall Height: . 1.400 inches Overall Width: . 1.375 inches Overall Overall Bode Diameter: Overall Width: . 1.375 inches Overall Overall Bode Diameter: Overall Overall Distance Between Mounting Facilities Parallel To Height: Overall Overall Distance Between Mounting Facilities Parallel To Height: Overall Overall Distance Between Mounting Facilities Parallel To Height: Overall Overall Distance Between Mounting Facilities Parallel To Height: Overall Overall Distance Between Mounting Facilities Parallel To Height: Overall Overall Distance Between Mounting Facilities Parallel To Height: Overall Overall Distance Between Mounting Facilities Parallel To Height: Overall Distance Between Centerlines Of Mounting Facilities Parallel To Height: Overall Distance Between Centerlines Of Mounting Facilities Parallel To Height: Overall Brade Distance Between Style: Overall Given Distance Between Style: Overall Given Distance Between Style: Overall Style Facilities Parallel To Height: Overall Parallel Distance Between Style: Overall Parallel Distance Between Style: Overall Parallel Distance Between Style: Overall Parallel Distance Between Center ID Style Distance Betwe	Thread Class:
Right-hand Body Style: Straight shape, external coupling Overall Length: 1.400 inches Overall Wight: 1.375 inches Overall Wight: 1.375 inches Overall Wight: 1.375 inches Unthreaded Mounting Hole Diameter: 0.120 inches Other To Center Distance Between Mounting Facilities Parallel To Height: 1.362 inches Other To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Hoight: 1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Contact Surface Treatment Eack single mating end single contact grouping Contact Material: Silver single mating end single contact grouping Contact Surface Treatment Silver single mating end single contact grouping Contact Surface Treatment Plastic polypropylene single mating end Single mating end single contact grouping Contact Surface Treatment Plastic polypropylene single mating end single contact grouping Contact Surface Treatment Plastic polypropylene single mating end single contact grouping Contact Surface Treatment Plastic polypropylene single mating end single contact grouping Sider well single mating end single contact grouping Contact Surface Treatment: Plastic polypropylene single mating end single contact grouping Sider well single mating end single contact grouping Sider well single mating end single contact grouping Sider well single mating end single contact grouping and gold single mating end single contact grouping Sider well single mating end single contact grouping Sider well single mating end single contact grouping	
Body Style: Straight shape, external coupling Overall Length: 1.400 inches Overall Height: 1.375 inches Overall Width: 1.375 inches Outhreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 1.821 single mating end Shell Type: Solid Contact Locking Method: Externally threaded shell Thread Size: 1.125 inches Thread Size: 1.25 ingle mating end single contact grouping Contact Material: Poper alloy single mating end single contact grouping Contact Material: Plastic polypropylene single mating end Biver single mating end single contact grouping and gold single mating end single contact grouping <	Thread Direction:
Straight shape, external coupling Overall Length: 1.400 inches Overall Height: 1.375 inches Overall Width: 1.375 inches Outhreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Conter Costion Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Cotact Surface Termenter: Silver single mating end single contact grouping and gold single mating end single contact grouping Charter Tarter To Center To Single mating end single contact grouping and gold single mating end single contact grouping Contact Surface Termenter: Silver s	Right-hand
Straight shape, external coupling Overall Length: 1.400 inches Overall Height: 1.375 inches Overall Width: 1.375 inches Outhreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Conter Costion Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Cotact Surface Termenter: Silver single mating end single contact grouping and gold single mating end single contact grouping Charter Tarter To Center To Single mating end single contact grouping and gold single mating end single contact grouping Contact Surface Termenter: Silver s	
Overall Length: 1.400 inches Overall Height: 1.375 inches Overall Width: 1.375 inches Unthreaded Mounting Hole Diameter: 0.120 inches Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Center lines Of Mounting Facilities Parallel To Body Width: 1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Concort Dostion Arrangement Style: Stall Type: Solid Connect Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Poper alloy single mating end single contact grouping Contact Material: Pister polypropylene single mating end Silver single mating end single contact grouping and gold single mating end single contact grouping Chartet Material: Pister polypropylene single mating end Silver single mating end single contact grouping and gold single mating end single	
1.400 inclusion 0verall Height: 1.375 inclusion 0verall Width: 1.375 inclusion 0verall Provide Mounting Hole Diameter: 0.120 inclusion 0verall Provide Provide Type: 1.062 inclusion Mating End Quantity: 1 0verall provide Type: Contact Position Arrangement Style: 1.821 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inclusion Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Material: Plastic polypropylene single mating end Silver single mating end single contact grouping and g	
1.375 indes Overall Width: 1.375 indes Unthreaded Mounting Hole Diameter: 0.120 indes Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 indes Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 indes Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 indes Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 indes Earterial Location: Back single mating end single contact grouping Contact Material: Coper alloy single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Biver single mating end single contact grouping Contact Surface Treatment: Plastic polypropylene single mating end <td< td=""><td>-</td></td<>	-
Overall Widh: 1.375 inches Unthreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Contact Locking Method: Externally threaded shell Thread Size: 1.125 inches Contact Surgle mating end single contact grouping Contact Material: Coper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Silver single mating end single contact grouping Contact Material: Plastic polypropylene single mating end Silver single mating end single contact grouping Silver single mating end single	Overall Height:
 1.375 inches Unthreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Hasterial: Plastic polypropylene single mating end Single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Ferminal Type: Solder well single mating end single contact grouping Chaterial: Plastic polypropylene single mating end Ferminal Type: Solder well single mating end single contact grouping 	1.375 inches
Uthreaded Mounting Hole Diameter: 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Single mating end single contact grouping and gold single mating end single contact grouping Hoster well single mating end single contact grouping Solder well single mating end single contact group	Overall Width:
0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Contact Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Silver single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Single mating end single contact grouping and gold single mating end single contact grouping Contact Material: Plastic polypropylene single mating end Single mating end single contact grouping and gold single mating end single contact grouping Contact Material: Plastic polypropylene single mating end Single mating end single contact grouping and gold single mating end single contact grouping Contact Waterial: Plastic polypropylene single mating end Single mating end single contact grouping Sidder well single mati	1.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Contect Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Silver single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Single mating end single contact grouping Solder well single mating end single contact grouping Solder well single mating end single contact grouping	Unthreaded Mounting Hole Diameter:
1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Silver single mating end single contact grouping and gold single mating end single contact grouping Silver single mating end single contact grouping and gold single mating end single contact grouping Contact Surface Treatment: Plastic polypropylene single mating end Solder well single mating end single conta	0.120 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Single mating end single contact grouping Affective Affectiv	Center To Center Distance Between Mounting Facilities Parallel To Height:
1.062 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Silver single mating end single contact grouping Charter Surface Treatment: Plastic polypropylene single mating end Terminal Type: Solder well single mating end single contact grouping	1.062 inches
Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Terminal Type: Solder well single mating end single contact grouping	Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Single mating end single contact grouping Cothact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Solder well single mating end single contact grouping Cothact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Figure Single mating end single contact grouping and gold single mating end single contact grouping Cothact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Figure Single mating end single contact grouping and gold single mating end single contact grouping Figure Single Material: Figure Single Material: Figure Single Mating End Single Contact grouping Figure Single Material: Figure Single Material: Figure Single Material: Figure Single Material: Figure Single Mating End Single Contact grouping Figure Single Material: Fig	1.062 inches
Mating End Quantity: 1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Plastic polypropylene single mating end Sider well single mating end single contact grouping Solder well single mating end single contact grouping	Threaded Device Type:
1 Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Plastic polypropylene single mating end Terminal Type: Solder well single mating end single contact grouping	Coupling facility
Contact Position Arrangement Style: 18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Terminal Type: Solder well single mating end single contact grouping	Mating End Quantity:
18-21 single mating end Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Silver well single mating end single contact grouping	1
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Solder well single mating end single contact grouping	Contact Position Arrangement Style:
Solid Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Single mating end single contact grouping and gold single mating end single contact grouping flasert Material:	18-21 single mating end
Connector Locking Method: Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Single mating end single contact grouping and gold single mating end single contact grouping Insert Material:	Shell Type:
Externally threaded shell Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Solder well single mating end single contact grouping Solder well single mating end single contact grouping	Solid
Thread Size: 1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Solder well single mating end single contact grouping	Connector Locking Method:
1.125 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Solder well single mating end single contact grouping Solder well single mating end single contact grouping	Externally threaded shell
Terminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Silver single mating end single contact grouping and gold single mating end single contact groupingInsert Material:Plastic polypropylene single mating endTerminal Type:Solder well single mating end single contact groupingShell Material:	Thread Size:
Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material:	1.125 inches
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material:	Terminal Location:
Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material:	Back single mating end single contact grouping
Contact Surface Treatment: Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material:	Contact Material:
Silver single mating end single contact grouping and gold single mating end single contact grouping Insert Material: Plastic polypropylene single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material:	Copper alloy single mating end single contact grouping
Insert Material: Plastic polypropylene single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material:	Contact Surface Treatment:
Plastic polypropylene single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material:	Silver single mating end single contact grouping and gold single mating end single contact grouping
Terminal Type: Solder well single mating end single contact grouping Shell Material:	Insert Material:
Solder well single mating end single contact grouping Shell Material:	Plastic polypropylene single mating end
Shell Material:	Terminal Type:
	Solder well single mating end single contact grouping
Aluminum alloy	Shell Material:
	Aluminum alloy

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Cadmium and chromate Included Contact Quantity: 3 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0