Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-230-0418

| view Online at https://aerobasegroup.com/nsn/5935-01-230-0418 | |
|--|--|
| Thread Direction: | |
| Right-hand | |
| Body Style: | |
| Straight shape, internal coupling | |
| Overall Length: | |
| 41.0 millimeters | |
| Overall Diameter: | |
| 49.7 millimeters | |
| Threaded Device Type: | |
| Back shell | |
| Mating End Quantity: | |
| 1 | |
| Contact Removability: | |
| Removable single mating end single contact grouping | |
| Polarization Method: | |
| Keyway or multiple keyway | |
| Insert Position In Deg: | |
| 0.0 | |
| Shell Type: | |
| Solid | |
| Connector Locking Method: | |
| Detent | |
| Thread Size: | |
| 37.0 millimeters | |
| Thread Pitch In Millimeters: | |
| 1.00 | |
| Terminal Location: | |
| Back single mating end single contact grouping | |
| Contact Material: | |
| Copper alloy single mating end single contact grouping | |
| Contact Surface Treatment: | |
| Gold single mating end single contact grouping | |
| Contact Surface Treatment Specification: | |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping | |
| Terminal Type: | |
| Crimp single mating end single contact grouping | |
| Shell Material: | |
| Aluminum alloy | |
| Shell Surface Treatment: | |
| Cadmium | |
| Shell Surface Treatment Specification: | |
| | |

Qq-p-416 federal specification single treatment response

NSN 5935-01-230-0418

Electrical Plug Connector - Page 2 of 2



Thread Tolerance Class:

6g external

Included Contact Quantity:

29 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.029 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

lso m

Specification Data:

81349-dod-c-38999/47 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.