Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-230-0430

| Thread Direction:  |
|--|
| Right-hand   |
| Body Style:  |
| Straight shape, internal coupling  |
| Overall Length:  |
| 41.1 millimeters   |
| Overall Diameter:  |
| 46.5 millimeters   |
| Threaded Device Type:  |
| Back shell   |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| 23-21 single mating end  |
| Contact Removability:  |
| Removable single mating end single contact grouping  |
| Polarization Method:   |
| Keyway or multiple keyway  |
| Insert Position In Deg:  |
| 0.0  |
| Shell Type:  |
| Solid  |
| Connector Locking Method:  |
| Detent   |
| Thread Size:   |
| 34.0 millimeters   |
| Thread Pitch In Millimeters:   |
| 1.00   |
| Terminal Location:   |
| Back single mating end single contact grouping   |
| Contact Material:  |
| Copper alloy single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Gold single mating end single contact grouping   |
| Contact Surface Treatment Specification:   |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type:   |
| Crimp single mating end single contact grouping  |
| Shell Material:  |
| Aluminum alloy   |
| Shell Surface Treatment:   |
| Nickel   |
|  |

# NSN 5935-01-230-0430

Electrical Plug Connector - Page 2 of 2



## Shell Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

## Thread Tolerance Class:

6g external

## Included Contact Quantity:

21 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.021 gold grains, troy

Precious Material:

Gold

### **Test Data Document:**

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

lso m

Specification Data:

81349-dod-c-38999/46 government specification

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.