## NSN 5935-01-230-0455

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-230-0455 **Body Style:** Straight shape **Overall Length:** 1.541 inches **Overall Height:** 0.663 inches **Overall Width:** 0.494 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 1.312 inches **Mating End Quantity: Contact Position Arrangement Style:** 15 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1250.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end and glass single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Shell Material:** 

Steel

**Shell Surface Treatment:** 

Cadmium and chromate

## NSN 5935-01-230-0455

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-m-14, ty gdi-30f or ty sd6-f military specification all material responses single mating end

**Included Contact Quantity:** 

15 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Special Features:** 

Mounting bracket included

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.015 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.