

NSN 5935-01-230-2205 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-230-2205 **Body Style:** Straight shape **Overall Length:** 1.335 inches **Overall Height:** 4.288 inches **Overall Width:** 0.305 inches **Environmental Protection:** Corrosion resistant and moisture resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.088 inches and 0.094 inches **Distance Between Mounting Facility Centers:** 1.115 inches **Mating End Quantity: Contact Position Arrangement Style:** 31 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

NSN 5935-01-230-2205

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

31 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.031 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0