NSN 5935-01-230-2224

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-230-2224

Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
34.16 millimeters
Overall Diameter:
26.78 millimeters
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
Afdx 11-5 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
100.0 and 260.0
Shell Type:
Solid
Connector Locking Method:
Detent
Thread Size:
15.0 millimeters
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel

NSN 5935-01-230-2224

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment Specification:	
Mil-c-26074, cl 3 or 4, grade b military specification single treatment response	
Thread Tolerance Class:	
6g external	
Included Contact Quantity:	
5 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.025 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	'n
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Iso m	
Specification Data:	
81349-dod-c-38999/49 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	