NSN 5935-01-230-2458

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-230-2458

Thread Class:
2a and 2b
Thread Direction:
Right-hand and left-hand
Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
1.735 inches
Overall Diameter:
1.466 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
18-11 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
0.0 Shell Type:
Shell Type:
Shell Type: Solid
Shell Type: Solid Connector Locking Method:
Shell Type: Solid Connector Locking Method: Externally threaded shell
Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20 and 10Thread Size:
Shell Type: Solid Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 20 and 10
Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20 and 10Thread Size:1.000 inches and 1.125 inchesTerminal Location:
Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20 and 10Thread Size:1.000 inches and 1.125 inches
Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20 and 10Thread Size:1.000 inches and 1.125 inchesTerminal Location:
Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20 and 10Thread Size:1.000 inches and 1.125 inchesTerminal Location:Back single mating end single contact grouping
Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20 and 10Thread Size:1.000 inches and 1.125 inchesTerminal Location:Back single mating end single contact groupingContact Material:
Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20 and 10Thread Size:1.000 inches and 1.125 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact grouping
Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20 and 10Thread Size:1.000 inches and 1.125 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingGold single mating end single contact groupingInsert Material:
Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20 and 10Thread Size:1.000 inches and 1.125 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingGold single mating end single contact groupingInsert Material:Further Single mating end single contact groupingRubber single mating end single contact grouping
Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20 and 10Thread Size:1.000 inches and 1.125 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingGold single mating end single contact groupingInsert Material:Rubber single mating end Single contact groupingContact Surface Treatment:Gold single mating end single contact groupingContact Surface Treatment:Rubber single mating endRubber single mating endRubber single mating endContact Surface Treatment Specification:
Shell Type:SolidConnector Locking Method:Externally threaded shellThready Qty Per Inch (tpi):20 and 10Thread Size:1.000 inches and 1.125 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingGold single mating end single contact groupingInsert Material:Further Single mating end single contact groupingRubber single mating end single contact grouping

Crimp single mating end single contact grouping

NSN 5935-01-230-2458

Electrical Plug Connector - Page 2 of 2



Shell Material: Aluminum **Shell Surface Treatment:** Anodize Included Contact Quantity: 5 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.025 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef and double stub Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.