NSN 5935-01-230-3462



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-230-3462 **Body Style:** Right angle type **Overall Length:** 7.840 inches **Overall Height:** 0.670 inches **Overall Width:** 0.493 inches **Environmental Protection:** Cold resistant and heat resistant and corrosion resistant and humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.097 inches **Distance Between Mounting Facility Centers:** 7.640 inches **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic polyamide single mating end

Terminal Type:

Pin single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Anodize

Included Contact Quantity:

207 single mating end single contact grouping

NSN 5935-01-230-3462

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type: Flat pin single mating end single contact grouping Special Features: 3 mtg tabs Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.207 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A039b0