## NSN 5935-01-230-4082

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-230-4082

Body Style:
Straight shape
Overall Length:
6.220 inches
Overall Height:
0.552 inches
Overall Width:
0.366 inches
Environmental Protection:
Cold resistant and heat resistant and humidity resistant and shock resistant and vibration resistant
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
End Application:
ADAP-TE-R,T-EST;
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, gr c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2
federal specification 2nd treatment response single mating end single contact grouping or mil-p-27418 military specification 2nd treatment
response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-b-626d federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single
material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end

## Insert Material Specification:

single contact grouping

Mil-m-14, ty sdg-f military specification all material responses single mating end

## **Included Contact Quantity:**

160 single mating end single contact grouping

Included Contact Type:

## NSN 5935-01-230-4082

Electrical Plug Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.160 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.