NSN 5935-01-230-9280

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-230-9280 **Thread Class:** 2g **Thread Direction:** Left-hand **Body Style:** Straight shape, internal coupling **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Internally threaded coupling nut Thready Qty Per Inch (tpi): 8 **Thread Size:** 2.000 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Metal single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber chloroprene class cr single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material:

Gold and silver

NSN 5935-01-230-9280

Electrical Receptacle Connector - Page 2 of 2



Thread Series Designator:
Special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.