NSN 5935-01-230-9282

Thread Class:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-230-9282

2b
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
Between 9.160 inches and 9.165 inches
Body Width:
0.640 inches
Body Height:
1.810 inches
Environmental Protection:
Shock resistant and vibration resistant and heat resistant and cold resistant
Distance Between Mounting Facility Centers:
1.970 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
500.0 single mating end single contact grouping
End Application:
4920-01-179-8469 adapter, test
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Side single mating end single contact grouping

Contact Surface Treatment:

Copper alloy single mating end single contact grouping

Contact Material:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-01-230-9282

Electrical Receptacle Connector - Page 2 of 2



Materia	

Plastic polyester single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Included Contact Quantity:

60 single mating end single contact grouping

Included Contact Type:

L-pin single mating end single contact grouping

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.060 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.