## NSN 5935-01-230-9667

Telephone Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-230-9667 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Body Style:** Threaded bushing mounted **Overall Length:** 1.440 inches **Mounting Bushing Length:** 0.400 inches **Overall Diameter:** 0.950 inches **Bushing Accommodation Hole Shape:** Round **Accommodated Finger Type:** Four conductor, jumbo spherical tip single finger **Finger Accommodation Diameter:** 0.282 inches single finger and 0.288 inches single finger **Finger Accommodation Length:** 0.802 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.695 inches **Jack Contact Arrangement Designator:** J2 **Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.688 inches **Terminal Type:** Tab, solder lug Material: Plastic, polyvinylidene fluoride insulator Material: Plastic polyvinylidene fluoride insulator **Surface Treatment:** Tin spring **Surface Treatment:** 

Tin spring

## NSN 5935-01-230-9667

Telephone Jack - Page 2 of 2



## **Test Data Document:**

81349-mil-c-9177 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

<del>-</del>	<b>~</b> · · · ·	<b>—</b>	
Inroad	SALIDE	LIDEIAN	Otor.
Thread	oci ico	Desidi	ialui.

Unef

## **Specification Data:**

81349-mil-c-9177/4 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03400