Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-231-1926

Body Style:	
Straight shape	
Overall Length:	
2.635 inches	
Overall Height:	
0.726 inches	
Overall Width:	
0.605 inches	
Environmental Protection:	
Vibration resistant and shock resistant	
Unthreaded Mounting Hole Diameter:	
0.120 inches	
Distance Between Mounting Facility Centers:	
2.406 inches	
Mating End Quantity:	
1	
Contact Removability:	
Removable single mating end 1st contact grouping	
Contact Maximum Current Rating In Amps:	
5.0 single mating end 1st contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
1000.0 single mating end 1st contact grouping	
Polarization Method:	
Mating end	
Shell Type:	
Solid	
Connector Locking Method:	
Friction	
Terminal Location:	
Back single mating end 1st contact grouping	
Contact Material:	
Copper alloy single mating end 1st contact grouping	
Contact Surface Treatment:	
Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping	
Insert Material:	
Plastic diallyl phthalate single mating end and glass fiber single mating end	
Contact Surface Treatment Specification:	
Mil-g-45204 military specification 1st treatment response single mating end 1st contact grouping and q	q-n-290 federal specification 2nd
treatment response single mating end 1st contact grouping	
Terminal Type:	
Crimp single mating end 1st contact grouping	
Contact Material Specification:	

Qq-c-530 federal specification single material response single mating end 1st contact grouping

Electrical Receptacle Connector - Page 2 of 2



Steel	
	Surface Treatment:
	nium and chromate
	Surface Treatment Specification:
	-416, class 2 or 3, type 2 federal specification all treatment responses
• •	Material Specification:
	-698 federal specification single material response
	t Material Specification:
	1-14, type gdi-30f or type sdg-f military specification all material responses single mating end
	ded Contact Quantity:
	ngle mating end 1st contact grouping
	ded Contact Type:
	d socket single mating end 1st contact grouping
	ious Material And Location:
	act surfaces gold
	ious Material And Weight:
) gold grains, troy
	ious Material:
Gold	
	Life:
N/a	
	Of Measure:
Demi	ilitarization:
No	
Fiig:	
A039	b0
	td (military Standard):
	-45204 spec.