NSN 5935-01-231-1927

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-231-1927

Body Style:
Straight shape
Overall Length:
2.078 inches
Overall Width:
0.492 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
1.852 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
25 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
25.0 single mating end single contact grouping
Polarization Method:
Mating and
Mating end
Connector Locking Method:
•
Connector Locking Method:
Connector Locking Method: Friction
Connector Locking Method: Friction Connector Cable Strain Relief Method:
Connector Locking Method: Friction Connector Cable Strain Relief Method: Bracket
Connector Locking Method: Friction Connector Cable Strain Relief Method: Bracket End Application:
Connector Locking Method: Friction Connector Cable Strain Relief Method: Bracket End Application: Receiving set, countermeasures
Connector Locking Method: Friction Connector Cable Strain Relief Method: Bracket End Application: Receiving set, countermeasures Terminal Location:
Connector Locking Method: Friction Connector Cable Strain Relief Method: Bracket End Application: Receiving set, countermeasures Terminal Location: Back single mating end single contact grouping
Connector Locking Method: Friction Connector Cable Strain Relief Method: Bracket End Application: Receiving set, countermeasures Terminal Location: Back single mating end single contact grouping Contact Material:
Connector Locking Method: Friction Connector Cable Strain Relief Method: Bracket End Application: Receiving set, countermeasures Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Connector Locking Method: Friction Connector Cable Strain Relief Method: Bracket End Application: Receiving set, countermeasures Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Connector Locking Method: Friction Connector Cable Strain Relief Method: Bracket End Application: Receiving set, countermeasures Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping
Connector Locking Method: Friction Connector Cable Strain Relief Method: Bracket End Application: Receiving set, countermeasures Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping Insert Material:
Connector Locking Method: Friction Connector Cable Strain Relief Method: Bracket End Application: Receiving set, countermeasures Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping Insert Material: Glass single mating end and plastic polycarbonate single mating end
Connector Locking Method: Friction Connector Cable Strain Relief Method: Bracket End Application: Receiving set, countermeasures Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping Insert Material: Glass single mating end and plastic polycarbonate single mating end Terminal Type:

Included Contact Type:

Round socket single mating end single contact grouping

NSN 5935-01-231-1927

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0