NSN 5935-01-231-2489

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-231-2489

Body Style:
Angle, shape, internal coupling
Overall Length:
1.313 inches
Overall Height:
8.750 inches
Overall Diameter:
0.420 inches
Environmental Protection:
Heat resistant and cold resistant and shock resistant and vibration resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
Bnc single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 and 120.0 and 240.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Crimp type
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, type 2, type
7 federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:

Qq-c-530, condition h federal specification single material response single mating end single contact grouping

Copper alloy

Shell Material:

NSN 5935-01-231-2489

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Qq-n-290, cl 2, type 7 federal specification single treatment response
Shell Material Specification:
Qq-b-626, composition 22, $1/2$ hard federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Special Features:
Unshielded cable type
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):